



Webhook Guide

BOX NOW WEBHOOK GUIDE

Ivan Bebek

BOX NOW D.O.O. | | OREŠKOVIĆEVA 6H/1, ZAGREB

Version	Date	Description	Author
1,0	2022-10-20	Initial document	Ivan Bebek
2,0	2023-12-05	Status update	Ivan Bebek
3,0	2024-05-06	Doc Update	Ivan Bebek
4,0	2025-08-25	Webhook data update	Ivan Bebek
5,0	2025-12-05	Full update	Ivan Bebek

Contents

Introduction.....	3
The available Webhook Event types are:	3
Hook Management.....	4
Webhook Description.....	4
Webhook Delivery.....	5
Problem Mitigation.....	5
Webhook Request Example.....	6
Testing Webhooks	7
Cross-referencing Webhook Events with the Tracking Page.....	7

Introduction

Partners need timely insight into events related to their parcels, and relying solely on time-based requests for updates is not an effective approach. Our Webhook functionality is designed to provide near real-time delivery of parcel state changes directly into partners' internal systems and applications. This supports partners who prefer not to depend on the <https://boxnow.gr> tracking page or who want to present tracking updates through their own mediums and channels.

Through the Webhook, partners receive notifications for all parcel status changes and events. Any events that are not relevant to a partner's workflow can be filtered and ignored on their side, as selective subscription to specific event types is not currently supported.

The available Webhook Event types are:

- **new** - Parcel has been registered to the system.
- **delivered** - Parcel has been delivered.
- **expired** - Parcel has expired and will return to the sender.
- **returned** - Parcel has been returned to the sender.
- **in-depot** - Parcel is at a BOX NOW Depot.
- **final-destination** - Parcel has reached its final destination waiting for pickup.
- **canceled** - Parcel has been canceled by the sender.
- **accepted-for-return** - Parcel has been accepted from customer and will be returned to the sender.
- **missing** - BOX NOW pickup courier was unable to obtain the parcel.
- **accepted-to-locker** - Parcel has been accepted from customer and will be sent to the recipient.

Hook Management

During the initial phase, BOX NOW will assist partners in configuring their webhook to the appropriate URL. Each partner receives a secret key to securely validate messages received from BOX NOW through data signing if needed.

Please ensure that webhook destination URLs are publicly accessible and explicitly use SSL Certificates from a public Certificate Authority (CA). If additional authentication is required, this can be managed through request headers.

Each partner can register only one webhook URL. If multiple internal systems need to receive webhook data, we recommend implementing a secure internal mechanism to relay the information after it has been received from BOX NOW.

Webhook Description

Although “**parcelState**” and “**event**” JSON properties appear similar, please rely on the “**event**” JSON property when parsing the status. This is required to ensure proper alignment with what end customers see on the tracking page.

The Webhook request schema conforms to the **CloudEvents** specification. This means that in a request you can find:

- **specversion** - The CloudEvents specification version (e.g., "1.0").
- **id** - A unique identifier for the event.
- **source** - A URI-reference indicating the event producer.
- **type** - A string describing the type of event.
- **time** - The time of webhook dispatch.
- **data.time** - time when the parcel event was created.
- **datasignature** - HMAC SHA256 digests of the request data that enables the recipient to verify integrity of received data. A partner must first obtain a secret key from us for decryption and verification.

In case multiple similar webhook requests are received in a short period, the client must use “**data.time**” to identify and filter out any invalid or duplicate updates.

Webhook Delivery

System makes N attempts to deliver a webhook request to your specified URL until the recipient responds with a successful message 200 OK.

Our **Retry Policy** uses exponential backoff with variable delays.

These variable delays are as follows:

1. After 5 Minutes
2. After 10 Minutes
3. After 1 Hour
4. After 2 Hours

Last attempt to deliver the hook is made 24 hours after event creation.

Webhook events are generated at specific points in the application through dedicated code snippets that automatically publish messages to Pub/Sub message queues.

This mechanism allows the system to emit structured event notifications whenever key operations occur, enabling partners systems to consume and process those events asynchronously.

Problem Mitigation

If we notice repeated unsuccessful responses to webhook requests, our team will reach out to inform you and help identify the issue. If the problem cannot be resolved promptly, we may temporarily disable the Webhook to give you space to address the situation.

All unsuccessful webhook requests are placed in a queue and delivered in order. This ensures that when a retry occurs, you receive the earlier pending requests first, following the process outlined above.

Webhook Request Example

```
POST {uri} HTTP/1.1
Content-Type: application/json

{
  "specversion" : "1.0",
  "type" : "gr.boxnow.parcel_event_change",
  "source" : "https://boxnow.gr/api/v1/webhooks/{id}",
  "subject" : "{ Parcel ID }",
  "id" : "{ Message ID }",
  "time" : "2022-09-16T11:06:04.296Z",
  "datacontenttype" : "application/json",
  "datasignature": "{ Box Now server event data integrity signature }"
  "data" : {
    "parcelId" : "{ Parcel ID }",
    "parcelState" : "{ Parcel State }",
    "parcelReferenceNumber" : "{ Parcel Reference Number }",
    "parcelName" : "{ Parcel Name }",
    "orderNumber" : "{ Order Number }",
    "event" : "{ Parcel Event }",
    "eventLocation" : {
      "displayName" : "{ Parcel location in a time of event }",
      "postalCode" : "{ Parcel location in a time of event }"
    },
    "customer" : {
      "name" : "{ Customer Name }",
      "email" : "{ Customer Email }",
      "phoneNumber" : "{ Customer Phone Number }",
    },
    "additionalInformation" : "{ Delivery Request additionalInformation }",
    "time": "2022-09-16T11:06:04.458Z"
  }
}
```

Some webhook requests may include additional attributes depending on the triggering event.

For instance, the **eventLocation** JSON object is not present in **"new"** or **"delivered"** events.

We recommend adjusting your parsers to avoid expecting every attribute in every request. After performing the necessary security checks, make your implementation more flexible in handling optional fields to ensure smooth processing.

Testing Webhooks

As with **Partner API** integrations, Webhook integrations should be initially tested in the Staging environment. Each environment will have its own Webhook Secret key (explained above), so please ensure you use the correct key when testing if you check the requests integrity.

BOX NOW is also available to support you in exploring full workflows and testing all relevant variables and events. This helps ensure everything functions as expected before moving to production.

Cross-referencing Webhook Events with the Tracking Page

For your convenience, here is a table that depicts how a customer would see the status of a parcel in the official BOX NOW Tracking page in comparison to the Webhook requests **“event”** types.

new	To be delivered by E-shop to BOX NOW	Čeka se preuzimanje iz e-trgovine
in-depot	Being delivered	Dostavlja se
final-destination	Your Parcel is located at the locker	Vaš paket se nalazi u pretincu
delivered	Your parcel has been delivered	Vaš paket je dostavljen
returned	Parcel has been returned	Paket je vraćen
expired	Expired return	Isteklo je vrijeme preuzimanja i paket je vraćen pošiljatelju
canceled	Canceled return	Paket je poništen
lost	To be found	Paket se pronalazi
missing	To be found	Paket se pronalazi
accepted-to-locker	Being delivered	U procesu isporuke
accepted-for-return	Being delivered	U procesu isporuke